



NOTES:

- (a) MAXIMUM SLOPE TRANSITION LENGTH MEASURED ALONG THE FACE OF CURB SHALL BE 15 FEET. A TRANSITION SLOPE GREATER THAN 7.5% IS ONLY ACCEPTABLE WHEN THE TRANSITION STONE REACHES A MAXIMUM LENGTH OF 15 FEET.
- (c) THE LANDING CROSS SLOPE (PARALLEL TO THE CURB LINE) AND THE GUTTER RUNNING SLOPE SHALL BE A MAXIMUM OF 1.5% AT APPROACHES UNDER STOP OR YIELD CONTROL. THE SLOPE MAY EXCEED 1.5% MAXIMUM UNDER THE FOLLOWING CONDITIONS:
 - SIGNAL OR PEDESTRIAN HYBRID BEACON= 4.5% MAX.
 - UNCONTROLLED = 4.5% MAX.
 - MIDBLOCK = NO GREATER THAN STREET GRADE
 - ROUNDABOUT = NO GREATER THAN STREET GRADE
- ± 0.5% MAX. CONSTRUCTION TOLERANCE PERMITTED ON ALL SLOPES.



**Public Works Department
Engineering Division**

1 CITY HALL SQUARE, ROOM 710
BOSTON, MA 02201
(617) 635-4968

**PEDESTRIAN RAMP - SIDEWALK
WIDTH LESS THAN 6.5'**

DATE OF ISSUE:
APRIL 2025

SCALE: N.T.S.

DETAIL NO.

R.3