



SECTION A - A

NOTES:

- (a) MAXIMUM SLOPE TRANSITION LENGTH MEASURED ALONG THE FACE OF CURB SHALL BE 15 FEET. A TRANSITION SLOPE GREATER THAN 7.5% IS ONLY ACCEPTABLE WHEN THE TRANSITION REACHES A MAXIMUM LENGTH OF 15 FEET.
- (b) THE LANDING CROSS SLOPE (PARALLEL TO THE CURB LINE) AND THE GUTTER RUNNING SLOPE SHALL BE A MAXIMUM OF 1.5% AT APPROACHES UNDER STOP OR YIELD CONTROL. THE SLOPE MAY EXCEED 1.5% MAXIMUM UNDER THE FOLLOWING CONDITIONS:
  - SIGNAL OR PEDESTRIAN HYBRID BEACON= 4.5% MAX.
  - UNCONTROLLED = 4.5% MAX.
  - MIDBLOCK = NO GREATER THAN STREET GRADE
  - ROUNDABOUT = NO GREATER THAN STREET GRADE
- ± 0.5% MAX. CONSTRUCTION TOLERANCE PERMITTED ON ALL SLOPES.



**Public Works Department  
Engineering Division**

1 CITY HALL SQUARE, ROOM 710  
BOSTON, MA 02201  
(617) 635-4968

## PEDESTRIAN RAMP - SIDEWALK WITH NON-WALKING AREA

**DATE OF ISSUE:**  
APRIL 2025

**SCALE:** N.T.S.

**DETAIL NO.**

R.4