

December 11, 2025

Outline

- 1) Introduction on Resiliency
- 2) Larger Project Vision
- 3) Building Level Threat and Resilience Approach
- 4) Key Considerations
- 5) Preferred Strategy Evaluation Design Approach
- 6) Dismissed Alternatives
- 7) Alignment with City of Boston schedule for efficiency and minimal disruption to the neighborhood
- 8) Next Steps
- 9) Appendix

December 11, 2025

1. Introduction on Resiliency





December 11, 2025

2. Larger Project Vision

2019 Masterplan + 2023 Building Level Resilience Assessment

Master Plan Guiding Principles



Activating our Waterfront

Creating a welcoming front yard for the Museum that accommodates a diversity of events, programs and experiences year-round.



Engaging our Children + Families

Inviting all visitors, whether young in years or young at heart, to immerse themselves in playful discovery at the water's edge.



Leading our Community's Resilience

Increasing the resilience of the Museum and surrounding district to the risks of sea level rise, climate change, and other socio-environmental challenaes.



Tomorrow's Museum Wharf

ARUP

The Boston Children's Museum | 308 Congress Street, Boston, MA Building-level Flood Resilience Assessment




Prepared by: Katie Wholey Kara Slocum, PE Derek Anderson, PE Michelle Silverwood

Date Issued: March 10, 20










December 11, 2025

3. Building Level Threat and Resilience Approach

Flooding Metrics – Project





2030 - 100 YEAR STORM ELEVATION



2050 - 100 YEAR STORM ELEVATION

PROJECT DESIGN FLOOD ELEVATION (DFE) *



2070 - 100 YEAR STORM ELEVATION



Project Site



Fort Point Channel Landmark District





Figure 2. MC-FRM 100-year Design Flood Elevations



Comparison of 100-year Design Storms

Current City of Boston Zoning Requirements dictate that any new construction or significant improvement would be required to meet at least a **14.0' design flood elevation**. (Article 25-A)

District scale requirements would dictate an even higher elevation.

100-year Design Storm			
Year	Elevation (NAVD88)*	Probability of event occurring between now and 2070	
Present Day	11.5	> 40%	
2030	12.5	> 33%	
2050	14.5	> 18%	
2070	16	1%	

^{*}Approximated from MC-FRM Model +1 ft freeboard

2070 — 2050 — 2030 —

Master Plan Passive Solutions (12.5-ft)

Master Plan Passive + Deployable Solution (14.5-ft)

Master Plan Modular Design and Recommended Building Design Flood Elevation (16.1-ft)






Phase 1: Protecting the historic walls


ARUP Official Recommended Dry Floodproofing Strategy as of the 2023 Resiliency Assessment Report

Excerpt from Building-Level Critical Resiliency Assessment for BCM (2023)

- Structural and Façade protection:
 - Structural recommendations for Strategy #2 can be found on pages 13 and 16 of the "Building-Level Resilience Assessment Report", dated March 10, 2023, as well as in Appendix B. The recommendations include:
 - Steel channel structural reinforcement at existing first floor masonry walls.
 - Structural reinforcement of the 2nd floor framing to account for increase load from relocated equipment. Assume 10 pounds per square foot (PSF) of steel reinforcement over area of equipment pad.
 - Install waterproof membrane over existing brick facade up to elevation 16-ft NAVD88 and extend to 1-ft below sidewalk.
 - Apply new brick veneer over waterproofing membrane and install a new underdrain at base of new veneer. See FEMA detail to further explain the approach:

Representative Recommended Strategy as of 2023 Critical Resiliency Assessment Report, FEMA P-259 2012)





December 11, 2025

4. Key Considerations


Key Considerations for a Long-Term Solution

- Necessary level of protection to ensure operations
 - Keeping the museum, an institution that serves the public, running
- Least impact on historic context of FPCLD, including appearance and materials
- Exterior vs. Interior
 - Balancing operational, economic, and visual impacts of the waterproofing solution on the museum
- Minimizing the public right-of-way encroachment
 - Property line delineation
- Integrated Initiatives
 - All phase 1 components work together to keep the museum dry
- Construction Timeline Alignment

December 11, 2025

5. Preferred Strategy Evaluation – Design Approach

Proposed Strategy – Extents of Treatment





Congress St Towards Atrium

Corner of Congress and Sleeper St

Proposed Strategy – Extents of Treatment





Sleeper St at Loading Dock


Boardwalk Side at Group Entry

Existing Wall Analysis – Material Inventory




Sleeper Steet Façade

Proposed Strategy – General Approach



Existing Condition




Proposed Approach

- Add waterproofing over existing brick, add new cladding to DFE
- Provide fittings for stop logs at openings.

Cladding Strategy

Single Wythe Brick






Conceptual Axonometric


Conceptual Section

Rendered Elevational View

Cladding Strategy

Single Wythe with Granite Watercourse (Preferred)







Rendered Elevational View

Cladding Strategy – Granite Watercourse Precedent

Single Wythe with Granite Watercourse (Preferred)



313 Congress St (Across the street)



303 Congress St (Across the street)



269 Summer St



263 Summer St



300 Congress St




Granite Base of 2006 Addition






Today's corrosion and damage to base bricks on Congress St


Proposed Strategy – View From Congress St and Sleeper St






Existing Proposed

Proposed Strategy – View From Congress St Towards Museum





Existing Proposed


Proposed Strategy – View From Sleeper St Toward Loading Area






Existing Proposed

Proposed Strategy – View From Boardwalk Towards Group Entry





Existing Proposed

December 11, 2025

6. Dismissed Alternatives

Relying on existing brick walls to keep water out Vetting Other External Potential Strategies (2025)

Leakage Rate Basis of Design:

- Based on 2011 testing conducted by David Perkes, AIA from Mississippi State University
- Cavity wall test box size: 3' x 3' x 4'
- After 22 hours, interior water depth was observed to be 36"
- Calculated leakage rate: 0.75 cft/hr/sft

Volume of flood water anticipated to enter Boston Children's Museum during 8-hour duration flood event: 174,000 gallons, equivalent to the volume of nine average in-ground swimming pools.




Image: 2011 MSU Test Set up
Test Pod B included brick cavity wall
system similar to Boston Children's
Museum wall construction

Passive Dry Floodproofing


Raise Building Above Flood Elevation

- Open foundations
 Not compatible with museum operations & substantial planning & cost
- Closed foundations
 Included

Soil fill
 Not compatible with museum operations & substantial planning & cost







Floodwalls and Levees

Earthen levees
 Included on west side of
 building; inadequate space
 along Sleeper & Congress
 Streets



Glass floodwalls
 Inadequate space



Concrete structures
 Inadequate space



Passive Dry Floodproofing

<u>Automatically-deployed</u> <u>flood barriers</u>

Hinged flood gates
 Inadequate space, long
 term risk



Backflow valves and pressure covers

 Backflow valves for pipes

Included




Flip-up barriers
 Inadequate space, long
 term risk





Pressure manhole coversNot applicable



Backflow valves for drains

Not applicable



Passive Dry Floodproofing

Sealants and Membranes


Waterproof membranes
 Included



Conduit seals
 Included







Stormwater Storage

Surface ponds
 Inadequate space



• Subsurface storage **Included**



• Bioretention areas **Inadequate space**



Deployable Dry Floodproofing

Flood Barriers

- Inflatable flood barriers
 Inadequate space, significant deployment time, long term risk
- Modular flood barriers
 Inadequate space,
 significant deployment
 time, long term risk
- Membrane barriers
 Inadequate space,
 significant deployment
 time, long term risk







Flood Shields

Door barriers
 Included



Window panelsIncluded



Log barriers
 Inadequate space,
 significant deployment
 time, long term risk



Wet Floodproofing

Building Modifications

Open crawlspaces
 Not compatible with
 museum operations &
 substantial planning and
 cost



Durable/resilient materials







Pumps and Drains Systems

Permanent sump pumpsIncluded



Portable sump pumpsIncluded




Floor drains
 Included






Protecting the historic walls Vetting Other External Potential Strategies




Strategy 1 – waterproofing applied to face of exterior brick.

- Least invasive
- Least effective
- Changes character
- Shorter maintenance cycle



Strategy 2 – Negative Side Waterproofing

- Most invasive
- Least effective



Strategy 3 – remove outer layer of existing brick, waterproof, install new brick

- Technically challenging
- Flush appearance
- Invasive, requires excavation of sidewalk
- Rise of freeze/thaw damage

Determined to be an inadequate solution due to the **poor external appearance** coupled with **durability** and **performance concerns** from leaving the membrane exposed

Determined to be an inadequate solution due to insufficient protection of the existing structure and potential for future issues + extensive and cost prohibitive demolition required

Determined to be **structurally infeasible** by Thornton Tomasetti combined with extreme **technical challenges** around installation.

Protecting the historic walls Dismissed Strategy 1



Strategy 1

- Apply opaque/semi-opaque fluid-applied waterproofing to face of exterior brick up to DFE.
- Provide fittings for stop logs at openings.







Challenges

- Significant detriment to appearance
- Loss of natural brick expression at street level
- Membrane left exposed and subject to damage

Protecting the historic walls Dismissed Strategy 2



2050 DFE



Extents of Interior Wall Demolition


Strategy 2

 Demolish all interior walls to apply a continuous new waterproofing membrane from the inside

Challenges

- Not feasible to maintain waterproofing continuity around timber floor structure
- Requires extensive demolition of all the interior walls along sleeper street to apply membrane to the interior
- Seawater exposure to the existing structural brick and timber beams degrades structural their integrity
- Water seepage into crawlspace is likely

Protecting the historic walls Dismissed Strategy 3



Challenges

- Determined to induce torsional forces within the load-bearing masonry, and thus structurally infeasible
- Flush solution creates risk of freeze/thaw due to lack of drainage plane behind replaced brick

Strategy 3

- Remove outer wythe of brick, waterproof, and install new brick flush with existing façade
- Provide fittings for stop logs at openings.

Boston Children's Museum – Fort Point Channel Landmark District Commission

December 11, 2025

7. Alignment with City of Boston's Schedule

SLEEPER STREET DESIGN COMPARISON





PREVIOUS DESIGN


- RAISED CROSSWALKS
- **SPEED HUMPS**
- **BIKE LANE WIDTH**


SIDEWALK WIDTH

- **ON-STREET PARKING SPACES**
- **CIRCULATION PATTERN**

- 5 feet on west side, 7 feet on east side
- 2 provided
- 3 provided
- No bike lane provided
- 20 provided
- Two-way

Sleeper Street City of Boston Early Coordination





UPCOMING PROCESS



NEXT STEPS

January - February 2025

March 2025

April 2025

Late Summer 2025

Permits approval?

April 2026

Tentative start of Construction at Sleeper Street

Spring 2028

Continuing Stakeholder Engagement

Complete Design, Public Improvement Commission

Construction Advertising

Construction Start (precise phasing TBD)

- Access to all residences and businesses will be maintained during the entire construction period.
- A full construction management and traffic management plan will be prepared by the selected contractor.
- Pre-construction notification will be provided to the community.
- Construction updates will be provided throughout the duration of the work.

Construction End

Substantial completion by the end of 2027 expected.

Boston Children's Museum – Fort Point Channel Landmark District Commission

October 9, 2025


8. Next Steps

Boston Children's Museum – Fort Point Channel Landmark District Commission


October 9, 2025

9. Appendix

Proposed Strategy – General Approach



Existing Condition



Proposed Approach


- Add waterproofing over existing brick, add new cladding to DFE
- Provide fittings for stop logs at openings.

Finalized Approach

Description

Pros:

Cons:



Conceptual Section




Rendered Elevational View

Finalized Approach

Description

Pros:

Cons:







Option A

Option B



Corner Detail